



GO WITH THE PRO!

BOSS

OILPRO™ BOSS FULL SYNTHETIC ATF - 295 is a new generation automatic transmission fluid that is suitable for use in applications where the OEM specifies a fluid providing performance capability comparable to the Allison TES 295® specification. As well as meeting the requirements of the JASO M315-2013 1. A specification for service fill fluid in the following automobile and truck transmissions, power-shift transmissions and other types of service: FCA (Chrysler ASRC); Ford (FNR5); Hyundai (ATF RED-1K, SP-III); Isuzu (Genuine ATF); Jaguar (K17); Kia (SP-III); Land Rover (AW-1, N402); Mazda (ATF M-V); Mitsubishi (ATF-J2, SP-III); Nissan (Fluid A, Matic D, J, K); Saab (ATF AP); Subaru (ATF HP, P/N K0140Y0700); Suzuki (Matic D, J); Toyota (JWS 3309, Type T, T-III, T-IV); VW (G 052 025)

May be used in the following applications:

Allison C-4	Suitable for Use
Audi G 052 025, 052 162, 055 025	Suitable for Use
BMW 7045E, LA2634, LT71141	Suitable for Use
BMW P/N 83 22 0 024 359, ETL-8072B	Suitable for Use
BMW P/N 83 22 0 0246 922, ETL-7045E	Suitable for Use
BMW P/N 83 22 0 403 249, ETL-8072B	Suitable for Use
BMW P/N 83 22 9 407 765, LA 2634	Suitable for Use
BMW P/N 83 22 9 407 807, LT 711 41	Suitable for Use
Dexron III G/H, Dexron II D/E, Dexron, AW1	Suitable for Use
Esso LT 71141	Suitable for Use
Ford Mercon, Ford ESP-M2C166-H	Suitable for Use
Ford P/N XT-2-DX (MERC), Ford P/N XT-2-SM (SYN MERC)	Suitable for Use
Ford XT8QAW	Suitable for Use
Fuchs 3353	Suitable for Use
Honda ATF Ultra II, DW-1, Z-1, 3.0, 3.1	Suitable for Use
Hyundai NWS 9638	Suitable for Use
Hyundai/Kia/Mitsubishi Diamond ATF-MA1, ATF PA, AW, J2, J3, SK, SP-II, SP-III, RED-1, SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SPH-IV, SP-IV-RR, JWS 3314,	Suitable for Use
IDEMITSU APOROIL ATF HP, Idemitsu K17 3100 PL085	Suitable for Use
ISUZU 08200-9001 / Genuine ATF	Suitable for Use
Jaguar P/N WSS-M2C922-A-1	Suitable for Use
JWS 3309, Any 3309	Suitable for Use
JWS 3324	Suitable for Use

ORDERING INFORMATION

PRODUCT	PACKAGE	PART #	PACKAGE	PART #
BOSS FULL SYNTHETIC ATF-295	- BULK -	# 01000400500ATF106	- DRUM -	# 01000400500ATF089
	- PAIL -	# 01000400500ATF081		

May be used in the following applications:

MAN 339 Type V2	Suitable for Use
MAN 339 Type Z1, Z2, V1	Suitable for Use
Mazda ATF M-III, MV, T-IV	Suitable for Use
MB236.1,2,5,6,7,9, 10, 11	Suitable for Use
MINI P/N 83 22 0 402 413	Suitable for Use
NAG-1 (Chrysler, Jeep, Cherokee)	Suitable for Use
Nissan Matic-D, J, K, 402	Suitable for Use
SAAB P/N 22 717 466, 93 165 147 (AW-1)	Suitable for Use
Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF, Saturn VI, 21005966, 1940700, 1940767, 22717466,88900925, 93160393,	Suitable for Use
Shell 3403 M115	Suitable for Use
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B	Suitable for Use
Subaru ATF, ATF-HP	Suitable for Use
Suzuki 3314, 3317	Suitable for Use
Texaco N402	Suitable for Use
Toyota T-II, T-III, T-IV, WS	Suitable for Use
Type A	Suitable for Use
Voith 55.6335 (G607)	Suitable for Use
Volvo P/N 1161540-8	Suitable for Use
Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342	Suitable for Use
VW G 052 162, 052 162 A1 A2 A6, 099, 055 025 A2	Suitable for Use
VW P/N GUS 000 162	Suitable for Use
Warren Distribution Recommends this product as suitable for use in applications specifying Allison TES-295	Suitable for Use
Warren Distribution Recommends this product as suitable for use in applications specifying Allison TES-389	Suitable for Use
ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C	Suitable for Use
ZF TE-ML 14B	Suitable for Use

OILPRO BOSS HD ATF 295	
Gravity, API	36.27
Density, lbs/gals	6.93
Flash, COC, °F	428
Viscosity	
@ 40 Degrees °F, cSt	32.3
@ 100 Degrees °F, cSt	7.4
Viscosity Index	195
Brookfield Viscosity	
cP @ -40°C	8,000
Color	Red



**2586 SOUTHPORT ROAD,
SPARTANBURG, SC 29302
1-800-922-3149**

ORDERING INFORMATION

PRODUCT	PACKAGE	PART #	PACKAGE	PART #
BOSS FULL SYNTHETIC ATF-295	- BULK -	# 01000400500ATF106	- DRUM -	# 01000400500ATF089
	- PAIL -	# 01000400500ATF081		