

# BOSS HEAVY DUTY MOTOR OIL

ollpro<sup>TM</sup> BOSS SYNBLEND HEAVY DUTY 10W30 is an API CK-4 fleet engine oil developed for use in four stroke cycle diesel engines designed to meet current highway exhaust emission standards. It is specially formulated to provide optimum performance in modern, low emission diesel engines operating under a wide variety of service conditions, including engines with cooled exhaust gas recirculation (EGR). It is blended with HVI base stocks and premium additive chemistry to achieve the following benefits: high temperature piston deposit control, foam protection, soot dispersancy and oil-thickening control, oxidation inhibition, low temperature sludge protection, corrosion and rust inhibition, valve train wear protection, TBN retention, and outstanding resistance to "shearing out" of viscosity grade. Recommended for use in turbocharged and naturally aspirated two and four cycle diesel engines. This engine oil also provides excellent performance in off-road service, including construction, forestry, mining, marine, and stationary power generation.

# **RECOMMENDED APPLICATIONS:**

## **MANUFACTURER**

**DETROIT DIESEL** 

**CUMMINGS** 

MACK

MACK

**RENAULT** 

VOLVO

**API CERTIFICATION** 

ACEA

CAT

MAN

**ALLISON** 

**DEUTZ** 

**FORD** 

### **SPECIFICATIONS**

DDC 93K222, DDC 93K223

CES 20086, 20087

**EO-O Premium plus** 

**EO-N, EOS-4.5** 

VI RLD- 4

**VDS-4.5** 

Number 2325 & CK-4

E7-16, E9-16

EFC-3

M3275, 3575

**TES 439** 

DQCIII-10LA

WSS-M2C171-F



### **TYPICAL VALUES**

Sp. Gr.		(W) cSt (@) 100°C		CCS @ -25°C	Phosphor us ppm		Zinc ppm	Sulfated Ash ppm	TBN
0.8685	82.18	11.9	140	5600 cP	1090	2300	1200	95	9.7

# **HEALTH, SAFETY & ENVIRONMENT**

### **HEALTH & SAFETY**

**OILPRO BOSS** is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained. Avoid contact with skin and use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from http://www.taylorlubricants.com

### **ENVIRONMENT**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.





2586 SOUTHPORT ROAD, SPARTANBURG, SC 29302 1-800-922-3149