



BOSS HEAVY DUTY MOTOR OIL

OILPRO™ BOSS SYNBLEND HEAVY DUTY 15W40 is an API CK-4/SN fleet engine oil developed for use in four stroke cycle diesel engines designed to meet current highway exhaust emission standards. It is specially formulated to provide optimum performance in modern, low emission diesel engines operating under a wide variety of service conditions, including engines with cooled exhaust gas recirculation (EGR). It is blended with HVI base stocks and premium additive chemistry to achieve the following benefits: high temperature piston deposit control, foam protection, soot dispersancy and oil-thickening control, oxidation inhibition, low temperature sludge protection, corrosion and rust inhibition, valve train wear protection, TBN retention, and outstanding resistance to “shearing out” of viscosity grade. Recommended for use in turbocharged and naturally aspirated two and four cycle diesel engines. This engine oil also provides excellent performance in off-road service, including construction, forestry, mining, marine, and stationary power generation.

RECOMMENDED APPLICATIONS:	
<u>MANUFACTURER</u>	<u>SPECIFICATIONS</u>
DETROIT DIESEL	DDC 93K222, DDC 93K223
CUMMINGS	CES 20086, 20087
MACK	EO-O Premium plus
MACK	EO-N, EOS-4.5
RENAULT	VI RLD- 4
VOLVO	VDS-4.5
API CERTIFICATION	2325, CK-4, CJ-4, CI-4+, CI-4, CH-4 & SN
ACEA	E7-16, E9-16
CAT	EFC-3
MAN	M3275, 3575
ALLISON	TES 439
DEUTZ	DQCIII-10LA
FORD	WSS-M2C171-F1



TYPICAL VALUES

Sp. Gr.	KV cSt @ 40°C	KV cSt @ 100°C	V.I.	CCS @ -25°C	Phosphorus ppm	Calcium ppm	Zinc ppm	Sulfated Ash ppm	TBN
0.8790	122	15.5	132	6500 cP	1100	2300	1250	90	9.7

HEALTH, SAFETY & ENVIRONMENT

HEALTH & SAFETY

OILPRO BOSS is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained. Avoid contact with skin and use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.taylorlubricants.com>

ENVIRONMENT

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

BOSS



2586 SOUTHPORT ROAD, SPARTANBURG, SC 29302
1-800-922-3149