



GO WITH THE PRO!

TO-4

TRANSMISSION + DRIVE TRAIN OILS

OILPRO TO-4 Transmission & Drive Train Oils are formulated to meet the performance requirements of Caterpillar Specification TO-4 and Allison C-4 for transmissions, final drives and hydraulic systems. The fluids are manufactured from selected, highly refined base stocks and compounded with additives to enhance oxidation and heat resistance, specified friction control, cleanliness, load-carrying ability, corrosion & wear protection and low foam tendency. OILPRO TO-4 has good detergent-dispersant characteristics.



TYPICAL PROPERTIES

SAE GRADE	SAE 10W	SAE 30W	SAE 50W
Viscosity, cSt			
mm ² /s @ 40°C	42.7	95.2	185.2
mm ² /s @ 100°C	6.5	11.0	17.3
Viscosity Index	102	100	100
Viscosity, Cold Crank Sim, -25°C	3250	-	-
Flash Point, (COC) Deg F (min)	400	425	460
Color, ASTM	2.0	3.0	4.5
TBN	7.5	7.5	7.5
Sulfated Ash %	1.2	1.2	1.2
Pour Point, Deg F	-25°	-10°	+5°
Gravity, API @ 60°F	30.0	28.5	27.0

ORDERING INFORMATION

PRODUCT	PACKAGE	PART #	PACKAGE	PART #	PACKAGE	PART #
10 W	- PAIL -	# 00910108800010081	- DRUM -	# 00910108800010089	- BULK -	# 00910108800010116
30 W	- PAIL -	# 00910108800030081	- DRUM -	# 00910108800030089	- BULK -	# 00910108800030116
50 W	- PAIL -	# 00910108800050081	- DRUM -	# 00910108800050089	- BULK -	# 00910108800050116