



## Synthetic Blend High Mileage 10W-30 SN PLUS

### INDUSTRY/OEM SPECIFICATIONS

API SN PLUS RC, SN RC	Approved
ILSAC GF-5	Approved
API SH, SG, SF, SE, SD, SC	Meets Requirements
API SL	Meets Requirements
API SM	Meets Requirements
GM 6094M	Meets Requirements
ILSAC GF-4	Meets Requirements

### TYPICAL PROPERTIES

Cold Cranking Simulator at (°C), cP	ASTM D5293	5,100 (-25)
Color	ASTM D1500	3
Flash Point °C	ASTM D92	206
Flash Point °F	ASTM D92	403
Noack Volatility, % loss	ASTM D6375	14.0
Pour Point, °C (°F)	ASTM D5950	-42°C (-44°F)
Pumping Viscosity at (°C), cP	ASTM D4684	15,000 (-30)
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.862
Sulfated Ash, wt. %	ASTM D874	0.92
TBN, mgKOH/g	ASTM D2896	7.3
Viscosity @ 40°C, cSt	ASTM D445	65.0
Viscosity @ 100°C, cSt	ASTM D445	10.2
Viscosity Index	ASTM D2270	144