



BOSS HEAVY DUTY FULL SYN AUTOMATIC TRANSMISSION FLUID - 295

BOSS HD Full Synthetic ATF is a new generation automatic transmission fluid meeting the requirements of the JASO M315-2013 1-A specification for service fill fluid in the following automobile and truck transmissions, power-shift transmissions and other types of service: FCA (Chrysler ASRC); Ford (FNR5); Hyundai (ATF RED-1K, SP-III); Isuzu (Genuine ATF); Jaguar (K17); Kia (SP-III); Land Rover (AW-1, N402); Mazda (ATF M-V); Mitsubishi (ATF-J2, SP-III); Nissan (Fluid A, Matic D, Matic J, Matic K); Saab (ATF AP); Subaru (ATF HP, P/N K0140Y0700); Suzuki (Matic D, Matic J); Toyota (JWS 3309, Type T, T-III, T-IV); VW (G 052 025).

BOSS HD Full Synthetic ATF is also recommended for service in the following automobile and truck transmissions, power-shift transmissions and other types of service, based on extensive testing: BMW (83 22 2 163 514, ETL-7045, ETL-7045 E, ETL-8072 B, LA2634, LT 71 141); FCA (Chrysler Type 7176E [+3], Type 9602 [+4]); Ford (P/N XT-2-QDX, P/N XT-5-QM); GM (6032M [IID], 6137M [IIE], 6417M [IIIG], 10055 [IIIH]); Honda (ATF-Z1); Mercedes (3403 M115, 236.1, 236.6, 236.7, 236.8, 236.9, 236.10, 236.11); Saab (ATF-Z1); VW (GUS 00 162). It is suitable for use in Voith Transmissions, as well as Allison Transmissions for extended drain.

BOSS HD Full Synthetic ATF is suitable for use in applications where the OEM specifies a fluid providing performance capability comparable to the Allison TES 295® specification.

BOSS HD Full Synthetic ATF is not certified by Allison Transmission under the TES 295® specification but meets testing requirements. Not for use in transmissions requiring Ford Type F, DEXRON®-VI, DEXRON®-HP, MERCON® SP, MERCON® LV, MERCON® ULV, Continuously Variable Transmission (CVT) or Dual Clutch Transmission (DCT).

BENEFITS

- Outstanding resistance to oxidative and thermal breakdown
- Exceptional low temperature fluidity
- Excellent anti-wear properties
- Excellent gear shift quality throughout service life
- Suitable for use in extended drain applications



May be used in the following applications:

Allison C-4	Suitable for Use
Audi G 052 025, 052 162, 055 025	Suitable for Use
BMW 7045E, LA2634, LT71141	Suitable for Use
BMW P/N 83 22 0 024 359, ETL-8072B	Suitable for Use
BMW P/N 83 22 0 0246 922, ETL-7045E	Suitable for Use
BMW P/N 83 22 0 403 249, ETL-8072B	Suitable for Use
BMW P/N 83 22 9 407 765, LA 2634	Suitable for Use
BMW P/N 83 22 9 407 807, LT 711 41	Suitable for Use
Dexron III G/H, Dexron II D/E, Dexron, AW1	Suitable for Use
Esso LT 71141	Suitable for Use
Ford Mercon, Ford ESP-M2C166-H	Suitable for Use
Ford P/N XT-2-DX (MERC), Ford P/N XT-2-SM (SYN MERC)	Suitable for Use
Ford XT8QAW	Suitable for Use
Fuchs 3353	Suitable for Use
Honda ATF Ultra II, DW-1, Z-1, 3.0, 3.1	Suitable for Use
Hyundai NWS 9638	Suitable for Use
Hyundai/Kia/Mitsubishi Diamond ATF-MA1, ATF PA, AW, J2, J3, SK, SP-II, SP-III, RED-1, SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SPH-IV, SP-IV-RR, JWS 3314,	Suitable for Use
IDEMITSU APOROIL ATF HP, Idemitsu K17 3100 PL085	Suitable for Use
ISUZU 08200-9001 / Genuine ATF	Suitable for Use
Jaguar P/N WSS-M2C922-A-1	Suitable for Use
JWS 3309, Any 3309	Suitable for Use
JWS 3324	Suitable for Use
MAN 339 Type V2	Suitable for Use
MAN 339 Type Z1, Z2, V1	Suitable for Use
Mazda ATF M-III, MV, T-IV	Suitable for Use
MB236.1,2,5,6,7,9, 10, 11	Suitable for Use
MINI P/N 83 22 0 402 413	Suitable for Use
NAG-1 (Chrysler, Jeep, Cherokee)	Suitable for Use
Nissan Matic-D, J, K, 402	Suitable for Use
SAAB P/N 22 717 466, 93 165 147 (AW-1)	Suitable for Use
Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF, Saturn VI, 21005966, 1940700, 1940767, 22717466,88900925, 93160393,	Suitable for Use
Shell 3403 M115	Suitable for Use
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B	Suitable for Use
Subaru ATF, ATF-HP	Suitable for Use
Suzuki 3314, 3317	Suitable for Use



May be used in the following applications:

Texaco N402	Suitable for Use
Toyota T-II, T-III, T-IV, WS	Suitable for Use
Type A	Suitable for Use
Voith 55.6335 (G607)	Suitable for Use
Volvo P/N 1161540-8	Suitable for Use
Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342	Suitable for Use
VW G 052 162, 052 162 A1 A2 A6, 099, 055 025 A2	Suitable for Use
VW P/N GUS 000 162	Suitable for Use
Warren Distribution Recommends this product as suitable for use in applications specifying Allison TES-295	Suitable for Use
Warren Distribution Recommends this product as suitable for use in applications specifying Allison TES-389	Suitable for Use
ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C	Suitable for Use
ZF TE-ML 14B	Suitable for Use

OILPRO BOSS HD ATF 295	
Gravity, API	36.27
Density, lbs/gals	6.93
Flash, COC, °F	428
Viscosity	
@ 40 Degrees °F, cSt	32.3
@ 100 Degrees °F, cSt	7.4
Viscosity Index	195
Brookfield Viscosity	
cP @ -40°C	8,000
Color	Red
Product Number	
BULK	01000400500ATF106
DRUM	01000400500ATF089
PAIL	01000400500ATF081



2586 SOUTHPORT ROAD,
SPARTANBURG, SC 29302
1-800-922-3149